



(19)

(11) Publication number: **200**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **11192469**(51) Intl. Cl.: **G11B 5/31 G11B 5/02 G11B**(22) Application date: **07.07.99**

<p>(30) Priority:</p> <p>(43) Date of application publication: 26.01.01</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: NEC CORP</p> <p>(72) Inventor: ISHI TSUTOMU</p> <p>(74) Representative:</p>
---	--

(54)

**MAGNETORESISTANCE
EFFECT COMPOSITE
HEAD, MAGNETIC
MEMORY DEVICE
EMPLOYING THE SAME,
AND MANUFACTURE OF
MAGNETORESISTANCE
EFFECT COMPOSITE HEAD**

(57) Abstract:

PROBLEM TO BE SOLVED: To obtain a magnetoresistance effect composite head which can prescribe a narrow magnetic pole with a writing width of not wider than 0.5 μm with a necessary and sufficient machining dimension tolerance.


SOLUTION: The magnetoresistance effect composite head comprises a magnetoresistance effect element 3 consisting of a spin valve element, an electrode part 5 adjacent to the element 3 and supplying a sensing current and 1st and 2nd magnetic shields 1 and 6 which hold the element 3 and the electrode part 5

Best Available Copy


between them with reading gaps 2a and 2b therebetween. The 2nd magnetic shield 6 is used as a 1st magnetic pole, and a writing magnetic gap 7, a coil (9), coil insulation parts (10a) and (10b), a 2nd magnetic pole 8 and a protective film 11 are formed on the 2nd magnetic shield 6 to compose an inductive head.

COPYRIGHT: (C)2001, JPO


(a)




(b)



(c)



(d)



Best Available Copy